


规格书 SPECIFICATION

PRODUCT NAME 产品名称	H07V-R	DOCUMEN NO 编号	PNTK-VR-004
SIZE 规格	1×16mm ²	Signature and seal of 客户签章	If you do not sign back, this specification is used by default. 如未回签，默认依此规格书。
SECTIONAL DRAWING 截面图	  Conductor: 导体 Sheath: 护套		

STANDARD BASIS 标准依据

EN50525-2-31

MARKING 印字	EARTH CABLE H07V-R 1×16mm ² Eca PNTech CE	
CONDUCTOR 导体	MATERIAL 材质	铜(Copper)
	CONSTRUCTION 结构(N/mm)	120/0.39±0.02AS
	DIA 绞合外径(mm)	5.0
INSULATION 绝缘	MATERIAL 材质	聚录乙烯(PVC)
	OVER DIAMEREDR 完成外径(mm)	7.6±0.2
	AVG. THICK 平均厚度(mm)	≥1.0
	MIN. THICK 最小厚度(mm)	≥0.8
	COLOR 颜色	依客户要求 Upon customer's request
SHEATH 护套	MATERIAL 材质	/
	OVER DIAMEREDR 完成外径(mm)	/
	AVG. THICK 平均厚度(mm)	/
	MIN. THICK 最小厚度(mm)	/
	COLOR 颜色	/
ELECTRICAL PERFORMANCE 电气性能	RATED VOLTAGE 额定电压(V)	1000V (max)
	RATED TEMP 额定温度(℃)	70℃
	COND. RESISTANCE 导体电阻(Ω/km, 20℃)	≤1.15
	INSU. RESISTANCE 绝缘电阻(MΩ.km, 70℃)	≥0.0056
	VOITAGE WITH STAND TEST 耐压试验	2.0KV, 5min
	SPARK ELECTROMECHANICAL VOLTAGE 火花机电压(KV)	8
PHYSICAL PROPERTY OF INSULATION 绝缘物理性能	MIN TENSILE STRENGTH 最小抗拉强度(N/mm ²)	≥12.5
	MIN BREAK ELONGATION RATE 最小断裂伸长率(%)	≥125
	FLAME TEST 燃烧测试	单根垂直燃烧
	ENVIRON MENT PROECTION 环保	ROHS
Packing specification 包装规格	包装数量: 100米 Packing quantity: 100m	

制作(PREPARED): 胡友冬

审核(CHECKED): 李方君

核准(APPROVED): 许红波